

Copper Bonded Grounding Rods



Dimension Rod Size Dia X Length	Actual Rod Dia	Thread Dia	Cat. No.
9.5 X 1200 (Un-threaded)	9.5	--	CER-012
9.5 X 1800 (Un-threaded)	9.5	--	CER-018
14 X 1200	12	14	CER-1412
14 X 1500	12	14	CER-1415
14 X 1800	12	14	CER-1418
14 X 2000	12	14	CER-1420
14 X 2400	12	14	CER-1424
5/8"X 4' or 16mm X 1200	14.2	5/8"	CER-1612
5/8"X 5' or 16mm X 1500	14.2	5/8"	CER-1615
5/8"X 6' or 16mm X 1800	14.2	5/8"	CER-1618
5/8"X 8' or 16mm X 2400	14.2	5/8"	CER-1624
5/8"X 10' or 16mm X 3000	14.2	5/8"	CER-1630
5/8"X 4' or 16mm X 1200	16	5/8"	CER- 412
5/8"X 5' or 16mm X 1500	16	5/8"	CER- 515
5/8"X 6' or 16mm X 1800	16	5/8"	CER- 615
3/4"X 4' or 20mm X 1200	17.2	3/4"	CER-1712
3/4"X 5' or 20mm X 1500	17.2	3/4"	CER-1718
3/4"X 8' or 20mm X 2400	17.2	3/4"	CER-1724
3/4"X10' or 20mm X 3000	17.2	3/4"	CER-1730

Solid Copper Grounding Rod & Accessories



ROD DETAILS	Diameter	Length	Cat. No.
	15mm	1200mm	CSCR-1512
	16mm	1200mm	CSCR-1612
	20mm	1200mm	CSCR-2012
ITEM	Size		Cat. No.
Driving Head	15mm		CDH-015
	16mm		CDH-016
	20mm		CDH-020
Driving Tip	15mm		CDT-015
	16mm		CDT-016
	20mm		CDT-020
Internal	M10		CCD-015
Coupling	M10		CCD-016
Dowel	M10		CCD-020